



## Carb ULS No.2 Diesel Clear Specifications Sheet

TYPICAL PROPERTIES	ASTM	MIN	TYPICAL	MAX
	Test Method			
API Gravity at 60 °F	<b>D287</b>		30	
Color	<b>D1500</b>		1.0	
Specific Gravity			0.8762	
Pounds per Gallon			7.296	
Flash Point, in °F, PMCC	<b>D93</b>	125	140	
Sulfur, PPM	<b>D5453</b>		6	15
Ash, wt. %	<b>D482</b>		< 0.01	0.01
Cloud Point, in °F	<b>D2500</b>		0	
Pour Point, in °F	<b>D97</b>		-75	
Ramsbottom Carbon Residue on 10% Dist. Residue, % Mass	<b>D524</b>		< 0.35	0.35
BS&W, vol. %	<b>D1796/D2709</b>		< 0.05	0.05
Cetane No.	<b>D613</b>	40	> 40	
Kinematic Viscosity mm/s at 40 °C	<b>D445</b>	1.9	3.8	4.1
Aromatics, Vol. Recovered	<b>D5186</b>		< 20	20
Distillation Temp in °F 90% Volume Recovered	<b>D86</b>	540	< 640	640
Copper Strip Corrosion Rating 3 H at 50 °C	<b>D130</b>		< NO.3	NO.3
Lubricity HFRR at 60 °C Micron, Max.	<b>D6079/D7688</b>		340	520
Conductivity, pS/m Min.	<b>D2624/D4308</b>	25	320	

T: 661-327-4257

F: 661-327-3236

3500 Shell Street, Bakersfield, CA 93308





## Carb ULS No.2 Diesel Red Specifications Sheet

TYPICAL PROPERTIES	ASTM	MIN	TYPICAL	MAX
	Test Method			
API Gravity at 60 °F	<b>D287</b>		30	
Color	<b>D1500</b>		1.0	
Specific Gravity			0.8762	
Pounds per Gallon			7.296	
Flash Point, in °F, PMCC	<b>D93</b>	125	140	
Sulfur, PPM	<b>D5453</b>		6	15
Ash, wt. %	<b>D482</b>		< 0.01	0.01
Cloud Point, in °F	<b>D2500</b>		0	
Pour Point, in °F	<b>D97</b>		-75	
Ramsbottom Carbon Residue on 10% Dist. Residue, % Mass	<b>D524</b>		< 0.35	0.35
BS&W, vol. %	<b>D1796/D2709</b>		< 0.05	0.05
Cetane No.	<b>D613</b>	40	> 40	
Kinematic Viscosity mm/s at 40 °C	<b>D445</b>	1.9	3.8	4.1
Aromatics, Vol. Recovered	<b>D5186-91</b>		< 20	20
Distillation Temp in °F 90% Volume Recovered	<b>D86</b>	540	< 640	640
Copper Strip Corrosion Rating 3 H at 50 °C	<b>D130</b>		< NO.3	NO.3
Lubricity HFRR at 60 °C Micron, Max.	<b>D6079/D7688</b>		340	520
Conductivity, pS/m Min.	<b>D2624/D4308</b>	25	320	

T: 661-327-4257

F: 661-327-3236

3500 Shell Street, Bakersfield, CA 93308

